

ICO Network Appliance



Specifications

CPU	Intel® 4th Generation Core™ i7/ i5/i3 / Xeon® processors
Chipset	Intel® C226 PCH Chipset
Memory	4x DDR3 DIMMs Max. 32GB, up to 1600MHz ECC or non-ECC
LAN	1x Intel® I217LM GbE PHY w/ iAMT 9.0 support 7x Intel® I210-AT GbE LAN 5/6 & 7/8 Bypass
Expansion Slot	1x mSATA socket 1x Mini PCI-E (mSATA compatible) socket 1 or 2 slots opening on rear panel
Storage	1x 2.5" / 3.5" HDD drive bay (depending on SKU) 1x CF socket 1x Dual 2.5" HDD drive bay (optional)
USB	2x USB 3.0 port on front panel Pin header for 6x USB 2.0 ports
Serial I/O	1x RJ45 console, COM2 pin header
VGA	Pin header
LED	Power / Bypass Activity / Status
Power Supply	Full range 300W ATX power supply or 275W 1+1 Redundant power supply
Dimensions	440 mm (W) x 411.5 mm (D) x 44 mm (H) 17.3"(W) x 16"(D) x 1.73"(H)
Operating Temperature	0°C~ 45°C (32°F~113°F)
Storage Temperature	-20° ~ 70°C (-4°F~158°F)
Operating Humidity	5~90%
Certification	CE/FCC

Features

- Supports Intel® 4th Generation Core™ i7/i5/i3 / Xeon® processors
- Advanced LAN Bypass
- 8x PCI-E GbE ports
- 4x DDR3 DIMMs, Max. 32 GB
- 3x system smart fans
- 1x CF socket, 1x Mini PCI-E (mSATA compatible)
1x mSATA socket
- iAMT 9.0

Accessories

MB968	LGA1150 for 4th Generation Core™ i7/i5/i3 / Xeon®, C226 PCH, 1x Intel® GbE I217LM + 7x Intel® GbE I210-AT, LAN 5/6 & 7/8 Bypass, SATA connector, Mini PCI-E, CF & PCI-E expansion
VGA4	VGA cable
IP331	1-to-1 PCI-E 8x riser card
IP332	PCI-E 8x adapter card
IP333	2-to-2 PCI-E 8x riser card
2.5" HDD Kit	Dual 2.5" HDD bracket
PK1-51	Console cable, 160cm
USB2-7	Dual port USB 2.0 cable, 300mm

Dimensions

